



# Product Information

www.miller-stephenson.com

## SolvSys™MS-580N / 582N Precision Cleaning Solvent

### Description

A nonflammable, precision solvent for critical cleaning of electronic components, circuits, precision instruments, electrical contacts, relays, and switching devices. Excellent for cleaning oils, grease, oxidation, and operating erosion dust. Evaporates quickly and leaves no residue.

### ADVANTAGES:

- Evaporates quickly
- Leaves no residue
- Nonflammable
- Non-ozone depleting
- RoHS Compliant

### Properties of Solvent:

Boiling Point..... 97°F /36°C  
 Flash Point.....None  
 Liquid Density.....1.32 g/ml @ 77°F/25°C  
 Ozone Depletion.....0.00

### Plastic Compatibility:

(Immersion: 15 minutes at Room Temperature)

- |                 |                        |
|-----------------|------------------------|
| • Acetal        | • Polyethylene         |
| • Polypropylene | • Polyester, PBT, PET  |
| • PEK, PEEK     | • Epoxy-Phenolics      |
| • Polyimides    | • Polyvinylchloride    |
| • PTFE          | • Liq. Crystal Polymer |

**NOTE:** Acrylic, ABS, and polycarbonate, if under stress, may show slight cracking or crazing damage. Test for compatibility before use.

### Elastomer Capability:

(Immersion: 15 mins at Room Temperature)

- |                       |                  |
|-----------------------|------------------|
| • Butyl Rubber        | • Natural Rubber |
| • Polysulfide         | • EPDM           |
| • Buna S              | • Buna N         |
| • Neoprene            | • Urethane       |
| • Chlorosulfonated PE | • Silicone       |
| • Viton™              |                  |

**NOTE:** Elastomer swelling and shrinking will, in most cases, revert to within a few percent of original size after air drying. Swell, shrinkage, and extractables are strongly affected by the compounding agents, plasticizers, and curing used in the manufacture of the elastomers. Test for compatibility before use.

### Metal Compatibility:

(Immersion: 2 weeks at 99°F/37°C)

- Aluminum
- Copper
- Iron

**Note:** Test for compatibility before use.

**Safety Data Sheets (SDS) are available upon request**

Viton™ is a trademark of The Chemours Company FC, LLC.

1594-9K

The recommendation made here with and the information set forth with respect to the performance or use of our products are believed, but not warranted to be accurate. The products discussed are sold without warranty, as to fitness or performance, express or implied and upon condition that purchasers shall make their own test to determine suitability of such products for their particular purposes. Likewise, statements concerning the possible uses of our products are not intended as recommendations to use our products in the infringement of any patent.