



1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Name: MS-555
DPMS-C0716A
Heavy Duty Solvent & Flux Remover

Product Use: Solvent Cleaning & Flux Removal
for electronic assemblies.

MANUFACTURER/DISTRIBUTOR:

Miller-Stephenson Chemical
55 Backus Ave.
Danbury, Conn. 06810 USA
(203) 743-4447

Emergency Phone Number:
(800) 424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

Flammable aerosol: Category 2
Acute toxicity (Oral): Category 4
Acute toxicity (Inhalation: vapor): Category 4
Specific Target Organ Toxicity (single exposure): Category 1
Aquatic Chronic: Category 3

Label elements:

Signal word
Danger

Pictograms



Hazard Statements

Flammable aerosol
Harmful if swallowed or if inhaled
Causes damage to organs (optic nerve)
Harmful to aquatic life with long lasting effects.

Precautionary Statements

Do not spray on an open flame or other ignition source.

Avoid breathing mist/vapors/spray.

Wash skin thoroughly after handling.

Do not eat, drink, or smoke when using this product.

Use in a well-ventilated area.

Avoid release to the environment.

IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If exposed: Call a poison center/doctor

Call a POISON CENTER or doctor/ physician, if you feel unwell.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Pressurized container: Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/ container in accordance with local, regional, national, and international regulations.

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. In high concentrations asphyxiation may occur. Victim may not be aware of asphyxiation. This material may make the heart more susceptible to arrhythmias. Catecholamines such as adrenaline, and other compounds having similar effects, should be reserved for emergencies and then used. Effects of breathing high concentrations of vapor may include: Tiredness or drowsiness. Convulsions. May cause cardiac arrhythmia. Prolonged skin contact may defat the skin and produce dermatitis.

3. INGREDIENTS

<u>Material (s)</u>	<u>CAS No.</u>	<u>Approximate %</u>
1,1,1,2,2,3,4,5,5,5-Decafluoropentane (HFC-43-10mee)	138495-42-8	22 - 26
Trans,1,2-Dichloroethylene	156-60-5	65 - 70
Methanol	67-56-1	4 - 6
Carbon Dioxide	124-38-9	3 - 4

4. FIRST AID MEASURES

Inhalation: Remove patient to fresh air. If not breathing, give artificial respiration. Give oxygen as necessary, if qualified personnel is available. Get medical attention if necessary.

Eye: Flush with large amounts of water for at least 15 minutes, lifting eyelids until no evidence of the chemical remains. Get medical attention. Remove contact lenses, if present and easy to do. Continue to rinse.

Skin: Wash skin with plenty of water for at least 15 minutes. Wash contaminated clothing before use. Get medical attention if necessary.

Oral: Do NOT induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Call a physician.

Most important symptoms/effects, acute and delayed: Harmful if inhaled. May cause respiratory irritation. Harmful if swallowed. Causes damage to organs (optic nerve). Swallowing a small quantity of this material will result in a serious health hazard. This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death. May cause eye irritation. Prolonged exposure may cause skin irritation.

5. FIRE FIGHTING MEASURES

Flammability: This product is flammable. **Test Method:** Ignition distance test and Enclosed space ignition test

Suitable Extinguishing Media: Alcohol resistant foam, Dry chemical, Carbon dioxide (CO₂)

Unsuitable extinguishing media: Do not use a heavy water stream. Use of heavy stream of water may spread the fire.

Special hazards: Hazardous reaction will not occur under normal conditions. Keep containers cool by spraying with water. Vapors may accumulate in confined spaces and are heavier than air.

Special Fire Fighting Instruction: Do not enter area without personal protective equipment. Exposure to decomposition products may be a hazard to health. Wear self-contained breathing apparatus, if necessary. Use water spray to keep exposed containers cool. Do not allow run-off from fire-fighting to enter drains or water sources.

6. ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel): Evacuate personnel to safe area. Use personal protective equipment. Remove all sources of ignition. Ventilate area, especially low or enclosed places where heavy vapors might collect. In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental precautions: Prevent material from entering sewers, waterways, or low areas. Should not be released into the environment.

Spill Cleanup: Contain spillage, and then collect with electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local / national regulations

7. HANDLING AND STORAGE

Handling: Keep away from open flame or other ignition sources. Use in a well-ventilated area to avoid breathing vapors. Vapors are heavier than air and accumulate in low areas. Use only with adequate ventilation. Use appropriate respiratory protection when ventilation is inadequate. When using do not eat, drink, or smoke. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

Storage Conditions: Store in a clean, dry place that is well-ventilated. Do not store near sources of heat, in direct sunlight or where temperatures exceed 125°F/52°C. Do not pierce or burn, even after use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Exposure Limits:</u>	<u>TLV (ACGIH)</u>	<u>PEL (OSHA)</u>	<u>AEL* (DuPont)</u>
1,1,1,2,2,3,4,5,5,5-Decafluoropentane	Not Established	Not Established	200 ppm, 8 & 12 Hr. TWA 400 ppm, Ceiling
Trans,1,2-Dichloroethylene	200 ppm, TWA	200 ppm, 8 Hr. TWA	200 ppm, 8 & 12 Hr. TWA
Methanol	200 ppm, TWA	200 ppm, 8 Hr. TWA	200 ppm, 8 & 12 Hr. TWA, Skin

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which is lower than the AEL are in effect, such limits shall take precedence.

Respiratory Protection: Avoid breathing vapors, mists or spray. Use with sufficient ventilation especially for enclosed or low places. Vapors are heavier than air and can cause suffocation by reducing oxygen. In poorly ventilated areas, use an approved self-contained breathing apparatus.

Eye Protection: Avoid eye contact. Use chemical goggles or safety glasses with side shields.

Skin Protection: Avoid contact with skin. Use gloves/protective clothing that impervious to this material when prolonged or frequently repeated contact occurs.

Prevention of Swallowing: Do not eat or drink when using this product. Wash exposed areas thoroughly with soap and water.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: N.A.

Percent Volatile by Volume: 100%

Density: 1.28 g/cc at 77°F/25°C

Vapor Pressure: To be determined

Vapor Density (Air=1): >1

Solubility in H₂O : To be determined

pH Information: Neutral

Evaporation Rate (CC14=1): N.A.

Form: Aerosol

Appearance: Clear

Color: Colorless

Odor: Ethereal

10. STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical stability: Stable at normal ambient conditions.

Possibility of hazardous reactions: Hazardous polymerization will not occur.

Material and Conditions to Avoid: Heat, sparks, flames. Direct sunlight. Extremely high temperatures. Strong acids, Strong bases and Strong oxidizers.

Decomposition: This product can be decomposed by high temperatures (flame, glowing metal surfaces, etc.) forming Carbon oxides (CO, CO₂), Hydrogen Chloride, Hydrogen fluoride, Carbonyl fluoride, Fluorocarbons.

11. TOXICOLOGICAL INFORMATION

Animal Data

1,1,1,2,2,3,4,5,5,5-Decafluoropentane (HFC-43-10mee)

Inhalation: 4 hour LC50: 114mg/l in rats, Central nervous system effects, Convulsions

Oral: LD50: > 5,000 mg/kg in rats

Dermal: LD50: > 5,000 mg/kg in rabbits

Skin Irritation: No skin irritation, rabbit

Eye Irritation: No eye irritation, rabbit

Skin Sensitization: Did not cause sensitization on laboratory animals., guinea pig

Repeated dose toxicity: Inhalation, rat

No toxicologically significant effects were found.

Reproductive toxicity: Animal testing showed no reproductive toxicity.

Teratogenicity: Animal testing showed no developmental toxicity.

Trans-1,2-Dichloroethylene

Oral: LD50: 7902 mg/kg in rats

Dermal: LD50: > 5,000 mg/kg in rabbits

Inhalation: 4 hour LC50: 95.4 mg/l in rats

Target Organs: Central nervous system, narcosis

Skin irritation: Mild skin irritation in rabbits

Eye irritation: Mild eye irritation in rabbits

Repeated dose toxicity: Inhalation, 90 days in rats: No toxicologically significant effects were found.

Oral, 90 days in rats: No toxicologically significant effects were found.

Mutagenicity: Did not cause genetic damage in animals.

Test on bacterial or mammalian cell cultures did not show mutagenic effects.

Reproductive toxicity: Animal testing showed no reproductive toxicity.

Teratogenicity: Animal testing showed no developmental toxicity.

Methanol

Inhalation Acute toxicity: 3mg/l, animals (unspecified species)

Target Organs: Central nervous system, Eye, Central nervous system effects, narcosis, eye effects.

Dermal Acute toxicity: 300 mg/kg in rabbits (unspecified species)

Target Organs: Central nervous system, Eye, Central nervous system effects, narcosis, eye effects.

Oral Acute Toxicity: 100 mg/kg, animals (unspecified species)

Target Organs: Central nervous system, Eye, Central nervous system effects: narcosis, eye effects

Skin irritation: Slight or no irritation, Rabbit

Eye irritation: Slight irritation, Rabbit

Skin sensitization: Did not cause sensitization on laboratory animals, Guinea pig

Carcinogenicity: Not classifiable as a human carcinogen. Overall weight evidence indicates that the substance is not carcinogenic.

Mutagenicity: Animal testing did not show any mutagenic effects.

Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Overall weight of evidence indicates that the substance is not mutagenic.

Did not cause genetic damage in animals.

Genetic damage in cultured mammalian cells was observed in some laboratory tests but not in others.

Genetic damage in cultured bacterial cells was observed in some laboratory tests but not in others.

Reproductive Toxicity: No toxicity or reproduction. Evidence suggests the substance is not a reproductive toxin in animals.

Teratogenicity: Evidence suggests the substance is not a developmental toxin in animals.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane (HFC-43-10mee):

96 hour LC50 in fathead minnows: 27.2 mg/L

96 hour LC50 in rainbow trout: 13.9 mg/L

48 hour LC50 in Daphnia magna: 11.7 mg/L

72 hour EC50 in green algae: > 120 mg/L

Trans-1,2-Dichloroethylene

96 hour LC50 in bluegill sunfish: 74 mg/l

48 hour LC50 in Daphnia magna: 79 mg/l

96 hour EC50 in green algae: 798 mg/l

Methanol

96 hour LC50 – Flathead minnow: 28,100 mg/l

48 hour EC50 – Daphnia (water flea): > 10,000 mg/l

96 hour LC50 – Green algae (Selenastrum carpicornutum): 22,000 mg/l

13. DISPOSAL CONSIDERATIONS

Comply with federal, state and local regulations. Remove to a permitted waste disposal facility.

14. TRANSPORT INFORMATION

U.S. DOT

Proper Shipping Name: Consumer Commodity

Hazard Class: ORM-D

Identification No. None

Packing Group: None

IATA

Proper Shipping Name: Aerosols, Flammable

Hazard Class: 2.1

Identification No. UN1950

Packing Group: None

IMDG

Proper Shipping Name: Aerosols, Flammable

Hazard Class: 2.1

Identification No. UN1950

Packing Group: None

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA: All ingredients are listed in TSCA inventory.

1,1,1,2,2,3,4,5,5-DECAFLUOROPENTANE (CAS# 138495-42-8) is controlled by TSCA Section 5, Significant New Use Rule (SNUR; 40 CFR 721.5645) The approved uses are: precision and general cleaning, carrier fluid, displacement drying, printed circuit board cleaning, particulate removal, film cleaning, process medium, heat transfer fluid (dielectric and non-dielectric), and test fluid. Processors and users of this substance must also comply with the applicable general SNUR requirements set forth in 40 CFR 721 subpart A, including export notification requirements if applicable (40 CFR 721.20), and the applicable record keeping requirements set forth at 40 CFR 721.125.

SARA 313 Regulated Chemicals: Trans-dichloroethylene, Methanol

State Regulations (U.S.)

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and/or birth defects or other reproductive harm.

16. OTHER INFORMATION

NPCA-HMIS Ratings:

Health - 2
Flammability - 2
Reactivity - 1

Personal Protective rating to be supplied by user depending on the conditions.

FOR INDUSTRIAL USE ONLY

REVISION DATE: SEPTEMBER 2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.