



1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Name: MS-745
DPMS T0407A2
Vertrel XSi

Product Use: Cleaning, Depositing or Swelling Silicone

MANUFACTURER/DISTRIBUTOR:

Miller-Stephenson Chemical
55 Backus Ave.
Danbury, Conn. 06810 USA
(203) 743-4447

Emergency Phone Number:
(800) 424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

Flammable aerosol: Category 1

Label elements:

Signal word

Danger

Pictogram



Hazardous warnings

Extremely flammable aerosol

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.

Take precautionary measures against static discharge.
Wear protective gloves/eye protection/face protection.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
Rinse skin with water/shower.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Pressurized container: Do not pierce or burn, even after use.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container to an approved waste disposal plant.

Other Hazards

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Prolonged skin contact may defat the skin and produce dermatitis. May cause cardiac arrhythmia. Misuse or intentional inhalation abuse may lead to death without warning.

3. INGREDIENTS

<u>Material (s)</u>	<u>CAS No.</u>	<u>Approximate %</u>
1,1,1,2,2,3,4,5,5,5-Decafluoropentane(HFC-43-10mee)	138495-42-8	40 - 50
Hexamethyldisiloxane	107-46-0	30 - 40
1,1,1,2-Tetrafluoroethane	811-97-2	18 - 22

4. FIRST AID MEASURES

Inhalation: Remove patient to fresh air, lie down. Keep patient warm and at rest. If not breathing, give artificial respiration. Give oxygen as necessary, if qualified personnel is available. Get medical attention if necessary.

Eye: Flush with large amounts of water for at least 15 minutes, lifting eyelids until no evidence of the chemical remains. Get medical attention. Remove contact lenses, if present and easy to do. Continue to rinse.

Skin: Wash skin with warm water after contact. Wash contaminated clothing before use. Get medical attention if necessary.

Oral: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Give 2 glasses of water. If vomiting occurs, lean victim forward to reduce the risk of aspiration. Call a physician.

Most important symptoms/effects, acute and delayed: No applicable data available.

Notes to Physician: Do not give adrenaline or similar drugs. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

5. FIRE FIGHTING MEASURES

Flammability: This product is flammable.

Test Method: Ignition distance test and Enclosed space ignition test

Autoignition Temperature: Not Determined

Flammable Limits in Air, % by Vol.: LEL: 5.0

UEL: Not Determined

Suitable Extinguishing Media: Water spray, Water mist, Dry chemical, Carbon dioxide (CO₂)

Unsuitable extinguishing media: No applicable data available.

Special hazards: Pressure build-up. Fire or intense heat may cause violent rupture of packages. Hazardous combustion products: Hydrogen fluoride Fluorinated hydrocarbons Carbonyl fluoride Carbon oxides.

Special Fire Fighting Instruction: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Wear neoprene gloves during cleaning up work after a fire. Exposure to decomposition products may be a hazard to health.

Further information: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Evacuate personnel to safe areas. Cool containers/tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel): Evacuate personnel to safe area. Ventilate area, especially low or enclosed places where heavy vapors might collect. In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental precautions: If containers rupture, prevent material from entering sewers, waterways, or low areas. Should not be released into the environment.

Spill Cleanup: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations

7. HANDLING AND STORAGE

Handling: Use in a well-ventilated area to avoid breathing vapors. Vapors are heavier than air and accumulate in low areas. Use only with adequate ventilation. Use appropriate respiratory protection when ventilations is inadequate. When using do not eat, drink, or smoke. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

Storage Conditions: Store tightly sealed in a clean, dry place, and well ventilated place. Do not store in temperatures that exceed 125°F/52°C, because the containers could leak or rupture from pressure and expansion. Protect from freezing temperatures. If solvent is stored below -10°C (14°F), mix prior to use

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Exposure Limits:</u>	<u>TLV(ACGIH)</u>	<u>PEL (OSHA)</u>	<u>AEL*(DuPont)</u>
1,1,1,2,2,3,4,5,5,5-Decafluoropentane	Not Established	Not Established	200 ppm, 8 & 12 Hr. TWA 400 ppm, Ceiling
Hexamethyldisiloxane	Not Established	Not Established	
1,1,1,2-Tetrafluoroethane	Not Established	Not Established	1000 ppm

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which is lower than the AEL are in effect, such limits shall take precedence.

Respiratory Protection: Avoid breathing vapors, mists or spray. Use with sufficient ventilation especially for enclosed or low places. Vapors are heavier than air and can cause suffocation by reducing oxygen. In poorly ventilated areas, use an approved self-contained breathing apparatus.

Eye Protection: Avoid eye contact. Use chemical goggles or safety glasses with side shields.

Skin Protection: Avoid contact with skin. Use gloves impervious to this material when prolonged or frequently repeated contact occurs.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: N.A.

Percent Volatile by Volume: 100

Density: 1.17 g/cc @ 77°F/25°C

Vapor Pressure: 135 mmHg @ 77°F/25°C

pH Information: Neutral

Solubility in H₂O: Slightly soluble

Form: Aerosol

Odor: Slight, ether-like

Color: Colorless

Appearance: Clear

10. STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and storage conditions.

Chemical stability: Product is chemically stable. No decomposition if stored and applied as directed.

Possibility of hazardous reactions: Vapors may form flammable mixture in air.

Material and Conditions to Avoid: Open flames and high temperatures. Alkali or alkaline earth metals. Powdered metal salts.

Decomposition: This product can be decomposed by high temperatures (flame, glowing metal surfaces, etc.) forming Fluorinated hydrocarbons, Hydrogen fluoride, Carbon dioxide, Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Animal Data

1,1,1,2,2,3,4,5,5,5-Decafluoropentane (HFC-43-10mee)

Inhalation: 4 hour LC50: 114mg/l in rats, Central nervous system effects, Convulsions

Oral: LD50: > 5,000 mg/kg in rats

Dermal: LD50: > 5,000 mg/kg in rabbits

Skin Irritation: No skin irritation, rabbit

Eye Irritation: No eye irritation, rabbit

Skin Sensitization: Did not cause sensitization on laboratory animals., guinea pig

Repeated dose toxicity: Inhalation, rat

No toxicologically significant effects were found.

Mutagenicity: Animal testing showed no mutagenic effects.

Reproductive toxicity: Animal testing showed no reproductive toxicity.

Teratogenicity: Animal testing showed no developmental toxicity.

Hexamethyldisiloxane

Inhalation: 4 hour LC50: 106mg/l, rat

Oral: LD50: > 12,160 mg/kg, rat

Dermal: LD50: > 2,000 mg/kg, rat

Skin Irritation: No skin irritation, rabbit

Eye Irritation: No eye irritation, rabbit

Skin Sensitization: Does not cause sensitization., human

Repeated dose toxicity: Ingestion, rat

No toxicologically significant effects were found.

Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Animal testing showed no mutagenic effects.

Reproductive toxicity: Animal testing showed no reproductive toxicity.

Teratogenicity: Animal testing showed no developmental toxicity.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane (HFC-43-10mee):

96 hour LC50 in fathead minnows: 27.2 mg/l

96 hour LC50 in rainbow trout: 13.9 mg/l

48 hour LC50 in Daphnia magna (water flea): 11.7 mg/l

72 hour EC50 in green algae: > 120mg/l

Hexamethyldisiloxane

96 hour LC50 in rainbow trout: 0.46 mg/l
72 hour ErC50 in *Desmodesmus subspicatus* (green algae): >32 mg/l
95 hour NOEC in *Pseudokirchneriella subcapitata* (green algae): 0.15 mg/l
48 hour EC50 in *Daphnia magna* (water flea): >11 mg/l

13. DISPOSAL CONSIDERATIONS

If recycling is not practicable, dispose of in compliance with local regulations. Remove to a permitted waste disposal facility. The product should not be allowed to enter drains, water courses or the soil.

14. TRANSPORT INFORMATION

U.S. DOT

Proper Shipping Name: Consumer Commodity
Hazard Class: ORM-D
Identification No. None
Packing Group: None

IATA

Proper Shipping Name: Aerosols, Flammable
Hazard Class: 2.1
Identification No. UN1950
Packing Group: None

IMDG

Proper Shipping Name: Aerosols, Flammable
Hazard Class: 2.1
Identification No. UN1950
Packing Group: None

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA: All ingredients are listed in TSCA inventory.

1,1,1,2,2,3,4,5,5,5-DECAFLUOROPENTANE (CAS# 138495-42-8) is controlled by TSCA Section 5, Significant New Use Rule (SNUR; 40 CFR 721.5645) The approved uses are: precision and general cleaning, carrier fluid, displacement drying, printed circuit board cleaning, particulate removal, film cleaning, process medium, heat transfer fluid (dielectric and non-dielectric), and test fluid. Processors and users of this substance must also comply with the applicable general SNUR requirements set forth in 40 CFR 721 subpart A, including export notification requirements if applicable (40 CFR 721.20), and the applicable record keeping requirements set forth at 40 CFR 721.125.

16. OTHER INFORMATION

NPCA-HMIS Ratings:

Health - 1

Flammability - 3

Reactivity - 1

Personal Protective rating to be supplied by user depending on the conditions.

FOR INDUSTRIAL USE ONLY

REVISION DATE: SEPTEMBER 2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.