



Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)

Version 3.0

Revision Date 10/13/2015

Ref. 150000001170

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)
Product Grade/Type	:	GPL: 200, 201, 202, 203, 204, 205, 206, 207, 207-500 XHT-S, XHT-SX, XHT-SZ NRT: 8900, 8904, 8906, PLSS Sealant: ST-45, ST-63 EG-2000, EG-3000 LVP, LS-23, AUT 2045, UM 04 PGL, TLC Grease KDP 4935
Product Use	:	Lubricant, For industrial use only.
Restrictions on use	:	Do not use product for anything outside of the above specified uses
Manufacturer/Supplier	:	The Chemours Company FC, LLC 1007 Market Street Wilmington, DE 19899 United States of America
Product Information	:	1-844-773-CHEM (outside the U.S. 1-302-773-1000)
Medical Emergency	:	1-866-595-1473 (outside the U.S. 1-302-773-2000)
Transport Emergency	:	CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)
Other information	:	professional use

SECTION 2. HAZARDS IDENTIFICATION

Not classified as a hazardous substance or mixture according to the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard 2012.

Other hazards



Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)

Version 3.0

Revision Date 10/13/2015

Ref. 150000001170

The product as such is not hazardous., The thermal decomposition vapours of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco., Repeated episodes of polymer fume fever may result in persistent lung effects.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

This product does not contain any components that require disclosure according to OSHA Hazard Communication Standard 2012.

SECTION 4. FIRST AID MEASURES

General advice	: When symptoms persist or in all cases of doubt seek medical advice.
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Oxygen or artificial respiration if needed.
Skin contact	: Wash with water and soap as a precaution.
Eye contact	: Rinse with plenty of water. If eye irritation persists, consult a specialist.
Ingestion	: Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Most important symptoms/effects, acute and delayed	: No applicable data available.
Protection of first-aiders	: If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Notes to physician	: Treat symptomatically.



Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)

Version 3.0

Revision Date 10/13/2015

Ref. 150000001170

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|--|
| Suitable extinguishing media | : The product itself does not burn.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : No applicable data available. |
| Specific hazards | : In fire conditions, toxic decomposition products may be formed. (see also section 10) |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus (SCBA). Wear suitable protective equipment. |
| Further information | : Standard procedure for chemical fires. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

- | | |
|-----------------------------|--|
| Safeguards (Personnel) | : Avoid contact with the skin and the eyes. Refer to protective measures listed in sections 7 and 8. |
| Environmental precautions | : Prevent material from entering sewers, waterways, or low areas. |
| Spill Cleanup | : Shovel into suitable container for disposal. |
| Accidental Release Measures | : No applicable data available. |

SECTION 7. HANDLING AND STORAGE



Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)

Version 3.0

Revision Date 10/13/2015

Ref. 150000001170

Handling (Personnel)	: Avoid breathing vapors from overheated material. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material. General industrial hygiene practice. Keep away from food and drink. Keep away from tobacco products. Wash hands and face before breaks and immediately after handling the product.
Handling (Physical Aspects)	: No applicable data available.
Dust explosion class	: No applicable data available.
Storage	: No special storage conditions required. Keep container closed to prevent contamination. No decomposition if stored and applied as directed.
Storage period	: No applicable data available.
Storage temperature	: No applicable data available.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls	: In the event that the polymer is heated above 300°C (572 F) local ventilation should be used to avoid exposure to fumes.
Personal protective equipment	
Respiratory protection	: No personal respiratory protective equipment normally required. In the case of hazardous fumes caused by overheating, wear self-contained breathing apparatus.
Hand protection	: Additional protection: No particular glove type is recommended, but nitrile may be used.
Eye protection	: Safety glasses
Skin and body protection	: No PPE is specified however, avoid contact with skin, eyes, and clothing. Preventive skin protection
Exposure Guidelines	
Exposure Limit Values	

**Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)**

Version 3.0

Revision Date 10/13/2015

Ref. 150000001170

This product does not contain any exposure limits that require disclosure according to OSHA Hazard Communication Standard 2012.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance**

Physical state : solid
Form : grease
Color : white

Odor : none

Odor threshold : No applicable data available.

pH : neutral

Melting point/freezing point : Melting point/range
320 °C (608 °F)

Boiling point/boiling range : No applicable data available.

Flash point : Method: Pensky-Martens closed cup - PMCC
does not flash

Evaporation rate : No applicable data available.

Flammability (solid, gas) : No applicable data available.

Upper explosion limit : No applicable data available.

Lower explosion limit : No applicable data available.

Vapour Pressure : No applicable data available.

Vapour density : No applicable data available.

Specific gravity (Relative density) : 1.89 - 1.93 at 24 °C (75 °F)



Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)

Version 3.0

Revision Date 10/13/2015

Ref. 150000001170

Water solubility	: insoluble
Solubility(ies)	: No applicable data available.
Partition coefficient: n-octanol/water	: No applicable data available.
Auto-ignition temperature	: No applicable data available.
Decomposition temperature	: 300 °C
Viscosity, kinematic	: No applicable data available.
Viscosity, dynamic	: No applicable data available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No applicable data available.
Conditions to avoid	: Decomposition temperature 320 °C (608 °F)
Incompatible materials	: No applicable data available.
Hazardous decomposition products	: Hazardous thermal decomposition products:: Fluorinated compounds

SECTION 11. TOXICOLOGICAL INFORMATION

Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)

Oral ALD - Approximate Lethal Dose	: > 11,000 mg/kg , Rat
Skin irritation	: slight irritation, Rabbit
Eye irritation	: slight irritation, Rabbit



Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)

Version 3.0

Revision Date 10/13/2015

Ref. 150000001170

Sensitisation : Animal test did not cause sensitization by skin contact., Guinea pig

Further information : The product contains no substances classified as hazardous to health in concentrations which should be taken into account.

Carcinogenicity

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

SECTION 12. ECOLOGICAL INFORMATION

Environmental Fate

Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)

Biodegradability : Not readily biodegradable.

Additional ecological information : The product contains no substances classified as hazardous to the environment in concentrations which should be taken into account.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal methods - Product : In accordance with local and national regulations.

Contaminated packaging : Dispose of container properly.
If recycling is not practicable, dispose of in compliance with local regulations.

SECTION 14. TRANSPORT INFORMATION



Krytox™ PFPE/PTFE Greases (GPL 20(X) Series)

Version 3.0

Revision Date 10/13/2015

Ref. 150000001170

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Restrictions for use : Do not use for medical-clinical purposes.

Krytox™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Revision Date : 10/13/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.